


Phone	Speed Dial Button	Speed Dial Destination
HQ phone 1	1	hq2@cisco.lab
HQ phone 1	2	br1@cisco.lab
HQ phone 1	3	bb@cisco.lab
HQ phone 2	1	hq1@cisco.lab
HQ phone 2	2	br1@cisco.lab
HQ phone 2	3	bb@cisco.lab
BR1 phone 1	1	hq1@cisco.lab
BR1 phone 1	2	hq2@cisco.lab
BR1 phone 1	3	bb@cisco.lab
BB phone	1	hq1@cisco.lab
BB phone	2	hq2@cisco.lab

SIP TRUNK:



Which three configuration tasks need to be completed on the router to support the registration of Cisco Jabber clients? (Choose three.)
 A. The DNS server has the wrong IP address.
 B. The internal DNS Service (SRV) records need to be updated on the DNS Server.
 C. Flush the DNS Cache on the client.
 D. The DNS AOR records are wrong.
 E. Add the appropriate DNS SRV for the Internet entries on the DNS Server.
 Answer: BCE

QUESTION 63 With Media Gateway Control Protocol configuration on the voice gateway, which three types of messages are involved in the call flow between the call agent and the voice gateway? (Choose three.)
 A. audit endpoint
 B. modify endpoint
 C. create connection
 D. delete notification
 E. restart in progress
 F. end connections
 Answer: ACE

QUESTION 64 Which task must you perform before deleting a transcoder?
 A. Delete the dependency records.
 B. Unassign it from a media resource group.
 C. Use the Reset option.
 D. Remove the device pool.
 E. Remove the subunit.
 F. Delete the common device configuration.
 Answer: B





QUESTION 65 How many active gatekeepers can you can define in a local zone?
 A. 1
 B. 2
 C. 5
 D. 10
 E. 15
 F. unlimited
 Answer: A

QUESTION 66 Company X has a Cisco Unified Communications Manager cluster and a VCS Control server with video endpoints registered on both systems. Users find that video endpoints registered on Call manager can call each other and likewise for the endpoints registered on the VCS server. The administrator for Company X realizes he needs a SIP trunk between the two systems for any video endpoint to call any other video endpoint. Which two steps must the administrator take to add the SIP trunk? (Choose two.)
 A. Set up a SIP trunk on Cisco UCM with the option Device-Trunk with destination address of the VCS server.
 B. Set up a subzone on Cisco UCM with the peer address to the VCS cluster.
 C. Set up a neighbor zone on the VCS server with the location of Cisco UCM using the menu option VCS Configuration > Zones > zone.
 D. Set up a SIP trunk on the VCS server with the destination address of the Cisco UCM and Transport set to TCP.
 E. Set up a traversal subzone on the VCS server to allow endpoints that are registered on Cisco UCM to communicate.
 Answer: AC

QUESTION 67 Scenario: There are two call control systems in this item. The Cisco UCM is controlling the DX650, the Cisco Jabber for Windows Client, and the 9971 Video IP Phone. The Cisco VCS and TMS controll the the Cisco TelePresence MCU, and the Cisco Jabber TelePresence for WindowsDP:



Locations:



After configuring the CFUR for the directory number that is applied to BR2 phone (+442288224001), the calls fail from the PSTN. Which two of the following configurations if applied to the router, would remedy this situation? (Choose two.) A. dial-peer voice 1 potsincoming called-number 228822....direct-inward-dialport 0/0/0:15B. dial-peer voice 1 potsincoming called-number 228822....direct-inward-dialport 0/0/0:13C. voice translation-rule 1rule 1/rt228821....S//+44&/exit ! voice translation-profile pstn-intranslate called 1!voice-port 0/0/0:15translation-profile incoming pstn-inD. voice translation-rule 1rule 1/rt228822....S//+44&/exit ! voice translation-profile pstn-intranslate called 1!voice-port 0/0/0:15translation-profile incoming pstn-inE. The router does not need to be configured. Answer: AD QUESTION 68Refer to the exhibit. Which configuration change is needed to enable NANP international dialing during MGCP fallback? A. Change the dial peer to dial-peer voice 901 voip.B. Change the dial peer to dial-peer voice 9011 pots.C. Add the command prefix 011 to the dial peer.D. Add the command prefix 9011 to the dial peer. Answer: C QUESTION 69Which statement is true regarding the configuration of SAF Forwarder? A. In a multisite dial plan, SAF Forwarders may exist in multiple autonomous systems.B. The client label that is configured in Cisco Unified Communications Manager must match the configuration on the SAF Forwarder router.C. There should not be multiple nodes of Cisco Unified Communications Manager clusters acting as SAF clients.D. The destination IP address must match the loopback address of the SAF router. Answer: A QUESTION 70Which technologies provide remote-site redundancy for Cisco IP Phones during a WAN failure? A. SRST and MGCP fallbackB. SRST and TEHOC. TEHO and MGCP fallbackD. SRST and AAR Answer: A !!!RECOMMEND!!! 1.|Braindump2go 2016.07 New Cisco 300-075 Exam PDF and VCE 355Q&As Dumps Instant Download:<http://www.braindump2go.com/300-075.html> [100% Exam Pass Promised!] 2.|Braindump2go 2016.07 New Cisco 300-075 Exam Questions PDF:<https://drive.google.com/folderview?id=0BwwEEerkugSaLZE0xZjQtcVgyNTA&usp=sharing>