

[2016-Mar.-NEW

2016 March Cisco CCNP Wireless 642-742 IUWVN Exam Questions Updated Today! **INTROCUCTION:The Implementing Cisco Unified Wireless Voice Networks (IUWVN) 642-742 exam is a 90-minute test with 55?75 questions associated with the Cisco CCNP Wireless certification. This 642-742 exam assesses a candidate's ability to integrate VoWLAN services into the WLAN and be able to implement QoS, MPLS, and high-bandwidth applications in the wireless network.** Exam Code: 642-742 Exam Name: Implementing Cisco Unified Wireless Voice Networks (IUWVN) Certification Provider: Cisco Corresponding Certification: CCNP Wireless 2016 642-742 IUWVN Study Guides:1. Describe and Design Voice Over Wireless Architecture2. Implement VoWLAN3. Implement QoS for Wireless Applications4. Implement multicast over wireless5. Prepare the Wireless Network for Video and High-Bandwidth Applications QUESTION 158What protocol can be enabled to listen in on IPv4 multicast streams and maintain a map of what each client requests on a wireless LAN controller? A. IGMPB. MLDC. PAPD. ICMPE. SIPF. NTP Answer: A QUESTION 159Which two security technologies should be used when deploying a 100 Wi-Fi phone installation? (Choose two.) A. Use WPA-PSK.B. Use IEEE 802.1X with unique users on each phone.C. Use the same IEEE 802.1X username on all phones.D. Use IEEE 802.1X and WEP 128.E. Use IEEE 802.1X and WEP 256.F. Use IEEE 802.1X and WPA2 and Cisco Centralized Key Management. Answer: BF QUESTION 160A customer wants FSR and certificate-based authentication. The solution must be simple to deploy. Which method should be used to meet the requirements? A. EAP-TLSB. PEAP-MSCHAPv2C. EAP-FASTD. PEAP-MSCHAPv2 machine authentication Answer: C QUESTION 161A network engineer is having wireless multicast fail when it hits the wired network.What command will show the source of multicast groups for troubleshooting? A. show ip igmpB. show ip mrouteC. show ip mcacheD. show ip interface countsE. show ip route Answer: B QUESTION 162An engineer is configuring a new VoWLAN and wants only IEEE 802.11g/n to be supported. Which two data rates should be configured? (Choose two.) A. 18 Mbps and higher should be supported.B. Lower than 24 Mbps should be supported.C. Lower than 11 Mbps should be disabled.D. 1, 2, 5.5, and 11 Mbps should be disabled.E. 11 Mbps should be mandatory.F. 6 and 9 Mbps should be supported.G. 12 Mbps should be mandatory. Answer: AG QUESTION 163 Which two critical requirements must be addressed in the RF site survey for wireless video surveillance? (Choose two.) A. packet lossB. jitterC. bandwidthD. channel selectionE. WLC configuration Answer: AB QUESTION 164A Cisco partner has finished completing a CUWN install for a healthcare customer. After completing the deployment, the support center has received a ticket stating the 7925 VoIP phones will not connect in a few of the remote offices. The phones display 'configuring IP' consistently. What would be the next step for troubleshooting? A. verify option 43 has been configuredB. verify option 150 has been configuredC. verify the DNS server has been configuredD. verify the domain name has been configured Answer: B QUESTION 165An engineer has been assigned the task of deciding the cell overlap for a wireless voice deployment. Which Cisco measurement recommendation should be considered? A. The edge of the cell should be -67 dBm.B. One AP should be deployed per 3000 square feet.C. The edge of the cell should be below 35 RSSI.D. The measurement should be done on the 2.4-GHz band. Answer: A QUESTION 166After enabling global multicast, multicast traffic has been flooding the wired and wireless network. The wireless engineer has been troubleshooting and is attempting to find the source of the traffic. What command will display the multicast traffic source as well as the incoming interface? A. show ip mrouteB. show ip igmp groupsC. show ip pim neighborD. show ip device tracking all Answer: A QUESTION 167A network engineer wants the DSCP marking to align with the 802.11e access category video. What will this marking be? A. 4B. 34C. 5D. AF31 Answer: B QUESTION 168Users are experiencing poor audio quality when calling from their 7925 series VoIP Phones. Call quality is exceptional from wired to wired phones, but not from wired to wireless phones. The wired network has QoS deployed properly and the SSID is configured with Platinum QoS. What should be verified to troubleshoot the issue? A. The controller is marking the 802.1p tag of 3, the AP switchport has been configured to trust DSCP, and the controller's switchport to trust CoS.B. The controller is marking the 802.1p tag of 4, the AP switchport has been configured to trust CoS, and the controller's switchport to trust DSCP.C. The controller is marking the 802.1p tag of 5, the AP switchport has been configured to trust DSCP, and the controller's switchport to trust CoS.D. The controller is marking the 802.1p tag of 6, the AP switchport has been configured to trust CoS, and the controller's switchport to trust DSCP. Answer: C

2016 NEW 642-742 IUWVN PDF & 642-742 IUWVN VCE 196Q Full
Version:<http://www.braindump2go.com/642-742.html>

Compared Before Buying CUWSS 642-742 PDF & VCE!		
Pass4sure	Braindump2go	Test King
	100% Pass OR Money Back	
Not In Stock	196 Q&As – Real Questions	Not In Stock
/	\$99.99	/
/	Coupon Code: BDNT2014	/