

[2017-Aug.-UpdatedExam Pass 100% !Braindump2go 300-175 Dumps 255Q Instant Download[87-100

[Full Version!]2017 August New Updated 300-175 Exam Dumps with PDF and VCE Free Share! Following are some new 300-175 questions: 1.[2017 New 300-175 Exam Dumps (PDF & VCE) 255Q&As Download:<https://www.braindump2go.com/300-175.html>
2.[2017 New 300-175 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNZjVxdkhhREFxblU?usp=sharing> QUESTION 87When upgrading a standalone Cisco UCS C-Series server, which method is correct? A. direct upgrade on all componentsB. Cisco Hardware Upgrade UtilityC. Cisco Host Upgrade UtilityD. Cisco Server Upgrade Utility Answer: C QUESTION 88In a standalone Cisco UCS C-Series server, which recommendations can be used to upgrade the BIOS? A. Cisco IMCB. Cisco UCS ManagerC. iFlash32 UtilityD. Flash ROM UtilityE. EFI InterfaceF. Cisco Host Upgrade UtilityG. USB Flash Utility Answer: F QUESTION 89What are the default settings of the Cisco IMCCIMC NIC properties on a standalone Cisco UCS C- Series server? A.

'Shared LOM' NIC mode with 'Active-active' NIC redundancy and DHCP enabledB. 'Shared LOM' NIC mode with 'Active-standby' NIC redundancy and DHCP enabledC. 'Dedicated' NIC mode with 'Active-standby' NIC redundancy DHCP disabledD. 'Dedicated' NIC mode with 'None' NIC redundancy and DHCP enabledE. 'Cisco Card' NIC mode with 'Active-active' NIC redundancy and DHCP enabled Answer: D QUESTION 90Which adapter is capable of supporting VM-FEX? A. VIC 1280B. Cisco UCS M61KR-IC. Cisco UCS M72KRD. Cisco UCS M51KR-B Answer: A QUESTION 91Which option does UEFI secure boot provide? A. checksum verification of the EFI shellB. certificate verification of the EFI shellC. checksum verification of the OSD. certificate verification of the OS Answer: D QUESTION 92Which component is unsupported by the UEFI boot device in the Cisco UCS C-series standalone? A. FlexFlash cardB. RAID arrayC. FCoED. iSCSIE. USBF. PXEG. PCI SSD Answer: G QUESTION 93Which statement about Cisco Integrated Management Controller secure mode is true? A. After you enable it, you cannot disable it.B. After you enable it, you cannot downgrade the Cisco Integrated Management Controller firmware.C. It verifies the OS before allowing it to boot.D. The server must reboot to apply. Answer: A QUESTION 94When implementing a Cisco UCS C-series standalone server, which of the following Cisco Integrated Management Controller NIC modes allow use of the least number of physical ports while providing maximum levels of redundancy? A. dedicatedB. shared LOMC. shared LOM 10GD. Cisco VIC Answer: D QUESTION 95Which option describes what Cisco Integrated Management Controller Network Security provides? A. protection against DDoS on the Cisco IMCB. a whitelist that specifies the servers allowed to access the Cisco IMCC. 802.1x support, allowing the Cisco IMC to log in to a port security networkD. user-configured ACLs to block known bad servers from accessing the Cisco IMC Answer: A QUESTION 96Which port type mode must be used on a Cisco UCS Manager for a SPAN port? A. eth-traffic-monB. eth-uplinkC. eth-serverD. eth-storage Answer: A QUESTION 97Where would you disable or enable Cisco Discovery Protocol? A. LAN connectivity policyB. service profileC. network control policyD. LAN uplinks manager Answer: C QUESTION 98Which three statements about default settings for fabric interconnect uplink ports are true? (Choose three.) A. When a VLAN is configured, it is trunked on all uplinks.B. Specific VLANs are trunked on specific uplinks.C. UDLD is enabled.D. UDLD is disabled.E. Cisco Discovery Protocol is enabled.F. Cisco Discovery Protocol is disabled.G. They connect to the I/O modules. Answer: ADE QUESTION 99Refer to the exhibit. An admin is configuring VLANs on a Cisco UCS B-Series vNIC. Which two statements about the traffic coming from the operating system with this configuration are true? (Choose two.)



A. The VLAN must be configured with ID 832 within the operating system.B. No VLAN tag should be added in the operating system.C. If traffic comes in untagged on this vNIC, it is placed in VLAN 832.D. This configuration is not supported when hypervisors are used.E. The uplink ports of the fabric interconnect have the native VLAN set to ID 832. Answer: BC QUESTION 100Refer to the exhibit. Which two statements about the fabric interconnect are true? (Choose two.)



A. The fabric interconnect forwards all broadcast packets on VLAN 311 out of each interface listed in the Membership.B. The fabric interconnect forwards broadcasts on VLAN 311 only when they are received on Po21.C. Without any changes to the switch, eth 1/32 could become the designated receiver for VLAN 311.D. All multicast traffic from a blade on VLAN 311 goes out of Po21.E. IGMP join packets from blades on VLAN 311 goes out Po21. Answer: BE !!!RECOMMEND!!! 1.|2017 New 300-175 Exam Dumps (PDF & VCE) 255Q&As Download:<https://www.braindump2go.com/300-175.html> 2.|2017 New 300-175 Study Guide Video: YouTube Video: [YouTube.com/watch?v=zm6ho1Bw02E](https://www.youtube.com/watch?v=zm6ho1Bw02E)