

[2017-New-Dumps100% Success-Braindump2go 2V0-622D PDF and VCE 140Q Instant Download[98-110

2017/November New Exam: VMware 2V0-622D Dumps with PDF and VCE Free Updated Today! Following are some new 2V0-622D Questions:1.[2017 New 2V0-622D Exam Dumps (PDF & VCE) 97Q&As Download:

<https://www.braindump2go.com/2v0-622d.html>2.[2017 New 2V0-622D Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNRG5abEhWMmJwN2M?usp=sharing>QUESTION 98When upgrading a standalone vCenter Single Sign-On Server version 5.5 to version 6.5, which will be the final deployment type?A. There is no option to do this type of upgrade.B. It will be an external Platform Services Controller.C. It will be an embedded Platform Services Controller with vCenter Server.D. It will be a Standalone vCenter Server.Answer: BQUESTION 99Which feature of vSphere networking protects hosts from losing connection to vCenter Server as a result of misconfiguration of the management network?A. NIC TeamingB. Private VLANC. RollbackD. Health CheckAnswer: CExplanation:By rolling configuration changes back, vSphere protects hosts from losing connection to vCenter Server as a result from misconfiguration of the management network.

<https://docs.vmware.com/en/VMware-vSphere/6.5/com.vmware.vsphere.networking.doc/GUID-8BA411A4-8582-4C02-8489-D3D7D09A9BF0.html>QUESTION 100VCSA backup can be backed up and sent to different location vis several different protocols.

Which are three of the supported protocols? (Choose three.)A. CIFSB. SCPC. HTTPD. FTPSE. AFPAnswer: BCD

Explanation:<https://www.vladan.fr/vmware-vcsa-6-5-backup-and-restore-how-to/>QUESTION 101For Virtual Machine

Compatibility upgrade, a VM needs to be in which power state?A. Maintenance modeB. SuspendedC. Powered OffD.

Powered OnAnswer: CExplanation:<https://pubs.vmware.com/vsphere-51/index.jsp?topic=%2Fcom.vmware.vsphere.upgrade.doc%2FGUID-60768C2F-72E1-42E0-8A17-CA76849F2950.html>QUESTION 102Which component must be deployed before using

encrypted virtual machines in a vSphere 6.5 environment?A. vCenter Server must use CA signed certificatesB. a host with supported Trusted Platform ModuleC. supported password vaultD. External Key Management ServerAnswer: DExplanation:

<https://docs.vmware.com/en/VMware-vSphere/6.5/com.vmware.vsphere.security.doc/GUID-E6C5CE29-CD1D-4555-859C-A0492E7CB45D.html>QUESTION 103Which system traffic type cannot be configured with Network I/O Control (NIOC) bandwidth

allocation?A. Virtual SAN trafficB. ESXi host Management trafficC. vSphere Replication trafficD. Software FCoE Adapter trafficAnswer: DQUESTION 104Which is the minimum number of hosts required for a VMware vSAN cluster to be able to apply a

vSAN RAID5 storage policy?A. six hostsB. three hostsC. four hostsD. five hostsAnswer: CExplanation:

<https://cormachogan.com/2016/02/15/vsan-6-2-part-2-raid-5-and-raid-6-configurations/>QUESTION 105Which three TCP/IP stacks are built in at the VMkernel level in vSphere 6 x? (Choose three.)A. Fault ToleranceB. vMotionC. ProvisioningD.

ManagementE. DefaultAnswer: ABCEExplanation:

<https://docs.vmware.com/en/VMware-vSphere/6.5/com.vmware.vsphere.networking.doc/GUID-D4191320-209E-4CB5-A709-C8741E713348.html>QUESTION 106In vSphere 6.5, a virtual machine is thinly-provisioned on a VMFS6 datastore. The administrator

deleted a large file within the guest OS. The freed blocks in the datastore are no longer needed by the VM.Which feature in vSphere 6.5 allows the backing storage to automatically reclaim the freed blocks?A. ATSB. DefragC. UNMAPD. Auto

ReclaimAnswer: CExplanation:Explanation:VAI UNMAP was introduced in vSphere 5.0 to allow the ESXi host to inform the backing storage that files or VMs had been moved or deleted from a Thin Provisioned VMFS datastore. This allowed the backing

storage to reclaim the freed blocks. There was no way of doing this previously, resulting in many customers with a considerable amount of stranded space on their Thin Provisioned VMFS datastores.QUESTION 107A new virtual machine cannot reach its

default gateway.- The vSphere administrator checks that the virtual machine's vmnic is connected to the correct portgroup, and that the portgroup is on the correct virtual switch- This is the only virtual machine on this portgroup- Other virtual machines that are on

the host and connected to the same Distributed switch are running as normal- The Distributed Switch has only one uplinkWhich could be the cause of this issue?A. Block All Ports has been selected on the Distributed Switch.B. The wrong VLAN ID has

been added to the portgroup.C. The VLAN has not been configured in virtual machine hardware settings.D. The physical adapter is down.Answer: DQUESTION 108Which two requirements must be met before enabling vSphere HA Application Monitoring for a

virtual machine? (Choose two.)A. VMware Tools must be installed on the VM.B. The vSphere Guest SDK must be installed on the VMs needing Application Monitoring.C. Application Monitoring requires that vCenter Server is linked to a working instance

of vRealize Operations Manager and the End Points Operations agent has been installed on the guest.D. Application Monitoring is only supported on Linux operating systems.E. Application Monitoring is only supported on Windows operating systems.Answer: AEQUESTION 109Which is true when assigning global permissions in a single vSphere Single Sign-On domain in a multi-site

configuration?
A. Users assigned global permissions will be able to access objects and solutions across all Single Sign-On domains in an organization.
B. Users assigned global permissions will be able to access objects and solutions only in the same Single Sign-On site.
C. Users assigned global permissions will have administrator access across all objects and solutions in a Single Sign-On domain.
D. Users assigned global permissions will be able to access objects and solutions within that Single Sign-On domain.
Answer: A
QUESTION 110
During Fibre Channel adapter setup of a ESXi host, which configuration guideline should be considered?
A. Do not mix Fibre Channel adapter models to access the same LUN from a single host unless the default queue depth has been changed.
B. Do not mix Fibre Channel adapters from different vendors in a single host.
C. Use Fibre Channel adapters from different vendors in a single host.
D. Set the queue depth to 16 if using a mix of different vendors' Fibre Channel adapters in all hosts in the cluster.
Answer: **B!!!RECOMMEND!!!**
1. |2017 New 2V0-622D Exam Dumps (PDF & VCE) 97Q&As
Download: <https://www.braindump2go.com/2v0-622d.html> |2. |2017 New 2V0-622D Study Guide Video: YouTube Video: [YouTube.com/watch?v=-4jSpOxI0RU](https://www.youtube.com/watch?v=-4jSpOxI0RU)