## [2017 NewsBraindump2go 400-151 VCE and PDF 372q Free Offered[286-300

2017 July CCIE 400-151 Exam Dumps with PDF and VCE New Updated in www.Braindump2go.com for Free Download Today! 100% Real Exam Questions! 100% Exam Pass Guaranteed! 1.|2017 New 400-151 Exam Dumps (PDF & VCE) 372Q&As Download:https://www.braindump2go.com/400-151.html 2.|2017 New 400-151 Exam Questions & Answers Download: https://drive.google.com/drive/folders/0B75b5xYLjSSNOUtSMndmVjV3czA?usp=sharing QUESTION 286Refer to the exhibit. Using which method is the host with MAC address (002a.6a5c0d44) learned? A. Local physical portB. Remote FabricPath modeC. Remote VTEPD. Remote router running NVEE. Local SVI Answer: C QUESTION 287Which option require by atomic counter to be laveraged in troubleshooting endpoint connectivity? A. Endpoint must be in different bridge domainB. Endpoint must connect to different leaf switchC. Endpoint must be in different endpoint groupD. end point must be in different VRFE. Endpoint must connect to the same leaf switch Answer: B QUESTION 288Which attribute is used to pass the user role back to the Nexus when remote AAA is enabled? A. Cisco AV-pairB. TACACS+ or RADIUS ack frame role attributeC. DH-CHAP challenge attributeD. privilege level attribute Answer: A QUESTION 289Which programming language is used to write custom workflow code in Cisco UCS Director? A. PythonB. Bash scriptC. Java scriptD. Java Answer: C QUESTION 290Which two statements about VACLs on Cisco Nexus 7000 Series Switches are true? (Choose two.) A. A single VACL can be shared across two or more VDCs.B. Use of VACLs requires no special license to be installed.C. VACLs make use of IP or MAC ACLs.D. Only options drop and forward are permitted. Answer: BC QUESTION 291Which language is used to write Cloupia Cscript? A. PythonB. UCS director macro languageC. JAVAD. Javascript Answer: D QUESTION 292Assuming the local peer is 10.0.0.1 and the remote peer (configuration not shown) is 10.0.0.2, which of these is used to configure PIM Anycast-RP on a Nexus 7000 switch? A. feature pim!interface loopback1ip address 10.0.0.1/32ip router ospf 10 area 0.0.0.0ip pim sparse-mode! interface loopback2ip address 2.2.2.2/32ip router ospf 10 area 0.0.0.0ip pim sparse-mode!ip pim anycast-rp 2.2.2.2 10.0.0.1ip pim anycast-rp 2.2.2.2 10.0.0.2ip pim rp-address 2.2.2.2 group-list 224.0.0.0/4B. feature pim!interface loopback1ip address 10.0.0.1/32 ip router ospf 10 area 0.0.0.0ip pim sparse-mode!interface loopback2ip address 2.2.2.2/32ip router ospf 10 area 0.0.0.0ip pim sparse-mode!ip pim anycast-rp 10.0.0.1 2.2.2.2ip pim anycast-rp 10.0.0.2 2.2.2.2ip pim rp-address 2.2.2.2 group-list 224.0.0.0/4C. interface loopback1ip address 10.0.0.1/32ip router ospf 10 area 0.0.0.0ip pim sparse-mode!interface loopback2ip address 2.2.2.2/32 ip router ospf 10 area 0.0.0.0ip pim sparse-mode!ip pim anycast-rp 2.2.2.2 10.0.0.1ip pim anycast-rp 2.2.2.2 10.0.0.2ip pim rp-address 2.2.2.2 group-list 224.0.0.0/4D. feature pimfeature msdp!interface loopback1ip address 10.0.0.1/32ip router ospf 10 area 0.0.0.0ip pim sparse-mode!interface loopback2ip address 2.2.2.2/32ip router ospf 10 area 0.0.0.0ip pim sparse-mode!ip msdp originator-id loopback1ip msdp peer 10.0.0.2 connect-source loopback1ip msdp description 10.0.0.2 To 7010-2ip msdp password 10.0.0.2 mypassword!ip pim rp-address 2.2.2.2 group-list 224.0.0.0/4 Answer: A QUESTION 293Which four options are part of Cisco ONE Enterprise Cloud Suite product portfolio? (Choose four.) A. Cisco Intercloud Fabric for BusinessB. Application Policy Infrastructure Controller C. Cisco Virtual Application Container Services D. Cisco Prime Service Catalog E. Cisco Open SDN ControllerF. Cisco UCS Director Answer: ACDF QUESTION 294You are setting up an ACI spine-leaf architecture and interconnecting the spine switches with the leaf switches. Which description of what happens after initial setup to activate these interlinks is true? A. The interlinks are Layer 2 connections and only the allowed VLAN list must be added.B. An overlay is created automatically, which creates a setup where the uplinks do not need to managed automatically.C. Fabric path must be configured on the interlinks.D. The Links are creating a Layer 3 network, and all links must be configured as point-to-point links. Answer: B QUESTION 295Which descripting of how to enable the Flex Flash Controller auto-sync function on the B200M4 blade is true? A. Configure a focal disk policy for FlexFlash.B. Enable auto-sync in the servers > inventory > storage subtab.C. Configure a storage policy for FX3S.D. Configure a storage connection policy to use auto-sync. Answer: B QUESTION 296 Which Cisco UCS Director feature enables you to view the REST API URL for every report displayed in Cisco UCS Director? A. report metadataB. orchestration feature setC. REST API BrowserD. automation feature set Answer: A QUESTION 297Which option lists valid configuration commands to help identify packet flow for ingress and egress IP packets and provide statistics based on packet flow when configuring a Cisco Nexus Device via the CLI? A. Flow Record, Flow Exporter, Flow MonitorB. sFlow Record, sFlow Exporter, sFlow MonitorC. NetFlow Record, NetFlow Exporter, NetFlowD. IPFix Record, IPFix Exporter, IPFix Monitor Answer: A QUESTION 298Which statement about IP-directed broadcast is true? A. When a directed broadcast packet reaches a switch that is directly connected to its destination subnet, that packet is "exploded" as a broadcast on the destination subnet B. An IP-directed broadcast is an IP packet whose destination address is a valid unicast address, but which originates from a node that is itself part of that destination subnetC. All switches in the network forward an IP-directed broadcast in the same way they forward unicast IP packetsD. An IP-directed broadcast is a packet whose destination address is a multicast group to send the

packet to a group of hosts in a local or remote network Answer: A QUESTION 299Which language is used to write Cloupia Csript? A. PythonB. Cisco UCS Director Macro languageC. JAVAD. JAVAScript Answer: D QUESTION 300In a Cisco USC B-Series environment, which option must the network adapters support to enable iSCSI boot? A. vNICB. CIMCC. iBFTD. UEFIE. MPIO Answer: C !!!RECOMMEND!!! 1.|2017 New 400-151 Exam Dumps (PDF & VCE) 372Q&As Download: https://www.braindump2go.com/400-151.html 2.|2017 New 400-151 Study Guide Video: YouTube Video: YouTube.com/watch?v=biFoBgnRT-I