


```

A. var client = new Service1Client();
   try
   {
       client.GetData(534);
   }
   catch (Exception e)
   {
       client.Abort();
       ...
   }
   finally
   {
       client.Close();
   }

B. var client = new Service1Client();
   using (client)
   {
       client.GetData(534);
       client.Abort();
   }

C. var client = new Service1Client();
   using (client)
   {
       client.GetData(534);
       client.Close();
   }

D. var client = new Service1Client();
   try
   {
       client.GetData(534);
       client.Close();
   }
   catch (Exception e)
   {
       client.Abort();
       ...
   }

```

A. Option AB. Option BC. Option CD. Option D Answer: D QUESTION 112 You are developing a Windows Communication Foundation (WCF) service. You establish that the largest size of valid messages is 8,000 bytes. You notice that many malformed messages are being transmitted. Detailed information about whether each message is malformed must be logged. You need to ensure that this information is saved in XML format so that it can be easily analyzed. What should you add to the service configuration file? A. `<messageLogging logMessagesAtServiceLevel="true" logMessagesAtTransportLevel="true" maxMessagesToLog="1000" maxSizeOfMessageToLog="8000" />` B. `<messageLogging logEntireMessage="true" logMalformedMessages="false" logMessagesAtServiceLevel="true" logMessagesAtTransportLevel="true" maxMessagesToLog="1000" />` C. `<message Logging logEntireMessage="true" logMalformedMessages="" false" logMessagesAtServiceLevel="true" logMessagesAtTransportLevel="true" maxMessagesToLog="1000" maxSizeOfMessageToLog="8000" />` D. `<messageLogging logEntireMessage="true" logMalformedMessages="true" logMessagesAtServiceLevel="true" logMessagesAtTransportLevel="true" maxMessagesToLog="1000" maxSizeOfMessageToLog="100000" />` Answer: D Explanation: To log malformed message we should set `logMalformedMessages="true"`, only D met this requirement QUESTION 113 You are developing a Windows Communication Foundation (WCF) service that executes a long-running operation. The service is accessed from your business applications in a server transaction in which the client does not participate. You need to ensure that the transaction times out and aborts if the operation has not completed within 45 seconds. What should you do? A. Set the service binding `sendTimeout` attribute to 00:00:45. B. Apply `[ServiceBehavior(TransactionTimeout="00:00:45")]` to the service implementation. C. Set the service binding `receiveTimeout` attribute to 00:00:45. D. Apply `[OperationBehavior(TransactionScopeRequired=false)]` to the service operation. Answer: B QUESTION 114 You are developing a new version of an existing message contract named `CustomerDetailsVersion1`. The new version of the message contract must add a `Department` field of type `String` to the SOAP header. You create a new class named `CustomerDetailsVersion2` that inherits from `CustomerDetailsVersion1`. You need to ensure that all client applications can consume the service. Which code segment should you use? A. `[MessageContract] public class CustomerDetailsVersion2 :`

CustomerDetailsVersion1 { [MessageHeader(MustUnderstand = false)] public string Department; } B. public class CustomerDetailsVersion2 : CustomerDetailsVersion1 { [MessageHeader(MustUnderstand = false)] public string Department; } C. [MessageContract] public class CustomerDetailsVersion2 : CustomerDetailsVersion1 { [MessageHeader(MustUnderstand = true)] public string Department; } D. public class CustomerDetailsVersion2 : CustomerDetailsVersion1 { [MessageHeader(MustUnderstand = true)] public string Department; } Answer: A QUESTION 115 You create a Windows Communication Foundation (WCF) service. It is deployed on Microsoft Internet Information Services (IIS) with an application pool running as Network Service. You enable WMI tracing before launching the service. Your IT support staff adds WMI data collection through ASP.NET WMI tracing. You need to restrict the collection of WMI data to a privileged account. What should you do in WMI Control in the Computer Management console? A. - Select the RootServiceModel namespace.- Remove Enable account permission for the Network Service account.- Add a custom user and grant that user Enable account permission. B. - Select the Rootaspnet namespace.- Remove Enable account permission for the Network Service account.- Add a custom user and grant that user Enable account permission. C. - Select the Rootaspnet namespace.- Remove Enable account permission for the Local System account.- Add a custom user and grant that user Enable account permission. D. - Select the RootSecurity namespace.- Remove Enable account permission for the Local System account. Answer: A Explanation:

<http://msdn.microsoft.com/en-us/library/ms735120.aspx> QUESTION 116 You are creating a Windows Communication Foundation (WCF) service. You have the following requirements:- Messages must be sent over TCP- The service must support transactions.- Messages must be encoded using a binary encoding- Messages must be secured using Windows stream-based security. You need to implement a custom binding for the service. In which order should the binding stack be configured? A. tcpTransport, windowsStreamSecurity, transactionFlow, binaryMessageEncoding B. transactionFlow, binaryMessageEncoding, windowsStreamSecurity, tcpTransport C. windowsStreamSecurity, tcpTransport, binaryMessageEncoding, transactionFlow D. binaryMessageEncoding, transactionFlow, tcpTransport, windowsStreamSecurity Answer: B QUESTION 117 You are developing a data contract for a Windows Communication Foundation (WCF) service. The data in the data contract must participate in round trips. Strict schema validity is not required. You need to ensure that the contract is forward-compatible and allows new data members to be added to it. Which interface should you implement in the data contract class? A. ICommunicationObject B. IExtension<T> C. IExtensibleObject<T> D. IExtensibleDataObject Answer: D QUESTION 118 A Windows Communication Foundation (WCF) service implements the following contract. [ServiceContract] public interface IHelloService { [OperationContract] [VVebGet(UriTemplate = "hello?name={name}")] string SayHello(string name); } The implementation is as follows. public class HelloService : IHelloService { public string SayHello(string name) { return "Hello " + name; } } The service is self-hosted, and the hosting code is as follows. WebServiceHost svcHost = CreateHostO; svcHost.OpenO; Console. ReadLineO; SrvHost.CloseO; You need to implement CreateHost so that the service has a single endpoint hosted at <http://localhost:8000/HelloService> which code segment should you use? A. WebServiceHost svcHost = new WebServiceHost(typeof(HelloService)); svcHost.AddServiceEndpoint(typeof(IHelloService), new WebHttpBinding(WebHttpSecurityMode.None), "<http://localhost:8000/HelloService>"); return svcHost; B. Uri baseAddress = new Uri("http://localhost:8000/"); WebServiceHost svcHost = new WebServiceHost(typeof(HelloService), baseAddress); svcHost.AddServiceEndpoint(typeof(IHelloService), new WebHttpBinding(WebHttpSecurityMode.None), "HelloService"); return svcHost; C. WebServiceHost svcHost = new WebServiceHost(new HelloServiceO); svcHost.AddServiceEndpoint(typeof(IHelloService), new WebHttpBinding(WebHttpSecurityMode.None), "<http://localhost:8000/HelloService>"); return svcHost; D. Uri baseAddress = new Uri("http://localhost:8000/"); WebServiceHost svcHost = new WebServiceHost(new HelloServiceO, baseAddress); svcHost.AddServiceEndpoint(typeof(IHelloService), new WebHttpBinding(WebHttpSecurityMode.None), "HelloService"); return svcHost; Answer: A QUESTION 119 You have a Windows Communication Foundation (WCF) service that accepts the following message contract. You need to ensure that the client sends a SOAP body that is accepted by the service.

```
[MessageContract (
    WrapperNamespace = "http://www.movieth
    ProtectionLevel = ProtectionLevel
public class Ticket
{
    [MessageBodyMember (
        Namespace = "http://www.movieth
        Order=1)]
    public DateTime ShowTime = DateT
    [MessageBodyMember (
        Namespace = "http://www.movieth
    public string ReservationName =
    [MessageBodyMember (
        Namespace = "http://www.movieth
    public int NumberOfSeats = 0;
}
```

A. <Ticket xmlns="http://www.movies.com"><NumberOfSeats xmlns="http://www.movietheater.com"></NumberOfSeats>
<ReservationName xmlns="http://www.movietheater.com" /> <ShowTime xmlns="http://www.movietheater.com">
2010-07-05T00:SI:10.0999304-05:00</ShowTime></Ticket>B. <Ticket xmlns="http://www.movietheater.com"><ShowTime
xmlns="http://www.movietheater.com">2010-07-05T00:51:10.0999304-05:00</ShowTime><ReservationName xmlns="
<http://www.movietheater.com>" /> <NumberOfSeats xmlns="http://www.movietheater.com"></NumberOfSeats> </Ticket>C.
<Ticket xmlns="http://www.movies.com"><ShowTime xmlns="http://www.movietheater.com">
2010-07-05TOO:51:10.0999304-05:00</ShowTime> <NumberOfSeats xmlns="http://www.movietheater.com"></NumbecOfSeats>
<ReservationName xmlns="http://www.movietheater.com" /> </Ticket>D. <Ticket xmlns="http://www.movietheater.com">
<ShowTime xmlns="http://www.movietheater.com">2010-07-05TOO:51:10.0999304-05:00</ShowTime><NumberOfSeats
xmlns="http://www.movietheater.com"></NumberOfSeats><ReservationName xmlns="http://www.movietheater.com" /> </Ticket>

Answer: C QUESTION 120 You are developing a custom service host for a Windows Communication Foundation (WCF) service. The service host is named MovieServiceHost. You need to deploy the service with the custom service host in Microsoft Internet Information Services (IIS) 7.0. What should you do? A. Create a factory for the custom service host. Name the factory MovieServiceHostFactory. In the web.config file, add the following attribute to the <add> element within the <serviceActivations> element, factory="HovieServiceHostFactory" B. Decorate the custom service host class with the following line. <System.ServiceModel.Activation.ServiceActivationBuildProvider()> C. Make sure that the service class has a default constructor. Add a public read-only property with the name ServiceHost that returns an instance of the MovieServiceHost class. D. Create a factory for the custom service host. Name the factory MovieServiceHostFactory. In the .svc file, add the following line. <%3 ServiceHost Service="MovieServiceHostFactory" Language="VB"%> Answer: A Braindump2go Offers PDF & VCE Dumps Download for New Released Microsoft 70-513 Exam! 100% Exam Success Guaranteed OR Full Money Back Instantly!

TS: Windows Cor
Microsoft .NET Fr



Questions and Answers : 341
Q&As
Updated: Nov 13, 2015
~~\$129.99~~ **\$99.99**
PDF DEMO
CHECK OUT

FREE DOWNLOAD: NEW UPDATED 70-513 PDF Dumps & 70-513 VCE Dumps from Braindump2go:
<http://www.braindump2go.com/70-513.html> (341 Q&A)