

Cisco 350-080 New Updated Exam Questions Download From Braindump2go Freely (141-150)

CISCO NEW UPDATED: New Updated 350-080 Exam Questions from Braindump2go 350-080 PDF Dumps and 350-080 VCE Dumps! Welcome to Download the Newest Braindump2go 350-080 VCE&PDF Dumps:

<http://www.braindump2go.com/350-080.html> (394 Q&As) Quick and Effective Cisco 350-080 Exam Preparation Options -

Braindump2go new released 350-080 Exam Dumps Questions! Cisco Official 350-080 relevant practice tests are available for


Instant downloading at Braindump2go! PDF and VCE Formates, easy to use and install! 100% Success Achievement Guaranteed!

Vendor: CiscoExam Code: 350-080Exam Name: CCIE Data Center Written Exam350-080 Dumps,350-080 Exam Dumps,350-080

Brainfump,350-080 Questions,350-080 VCE,350-080 PDF,350-080 Actual Test,350-080 Study Guide,350-080 Book,350-080 CCIE

Data Center Written Exam,350-080 Test

CCIE Data Center Written Exam: 350-080



Product Description Exam Number/Code: 350-080

Exam Number/Code: 350-080

"CCIE Data Center Written Exam", also known as 350-080 exam, is a Cisco Certification. With the complete collection of questions and answers, Braindump2go has assembled to take you through 394 Q&As to your 350-080 Exam preparation. In the 350-080 exam resources, you will cover every field and category in Cisco CCIE Data Center helping to ready you for your successful Cisco Certification.

Questions and Answers : 394 Q&As

Updated: Oct 12, 2015

~~\$129.99~~ **\$99.99**

[PDF DEMO](#)

[CHECK OUT](#)

Free Demo Download

Braindump2go offers free demo for 350-080 exam (CCIE Data Center Written Exam). You can check out the interface, question quality and usability of our practice exams before you decide to buy it.

Printable PDF Premium VCE + VCE Simulator

QUESTION 141 Which three flow-control port states lead to enabled link flow control? (Choose three.) A. Receive port: Enabled, Transmit port: Enabled B. Receive port: Enabled, Transmit port: Desired C. Receive port: Enabled, Transmit port: Disabled D.

Receive port: Disabled, Transmit port: Desired E. Receive port: Desired, Transmit port: Desired Answer: ABE QUESTION 142

You can install Cisco DCNM-LAN on a supported version of which two operating systems? (Choose two.) A. Microsoft Windows Server B. Novell SUSE Linux Enterprise Server C. Oracle Enterprise Linux D. Red Hat Enterprise Linux E. VMware ESX

Answer: AD QUESTION 143 Cisco DCNM-LAN supports the configuration and monitoring of many Cisco NX-OS features, including which two of these Ethernet protocols? (Choose two.) A. GLBP B. HSRP C. IRDP D. VRRP Answer: AB


QUESTION 144 The vPC peer-gateway capability allows a vPC switch to act as the active gateway for packets that are addressed to the router MAC address of the vPC peer. This feature enables local forwarding of such packets without the need to cross the vPC peer link. Which statements are true about the vPC peer-gateway? (Choose two.) A. The vPC peer-gateway feature is enabled by default. B. The vPC peer-gateway feature can be configured globally under the vPC domain submode. C. Enabling the

peer-gateway feature automatically disables IP redirects on all interface VLANs mapped over a vPC VLAN to avoid generation of IP redirect messages for packets switched through the peer gateway router. D. The vPC peer-gateway feature only works with HSRP protocol. Answer: BC QUESTION 145 DHCP snooping on Cisco Nexus 1000V Series Switches acts like a firewall between untrusted hosts and trusted DHCP servers by doing which of these? (Choose three.) A. validates DHCP messages received from untrusted sources and filters out invalid response messages from DHCP servers B. intercepts all ARP requests and responses on untrusted ports C. builds and maintains the DHCP snooping binding database, which contains information about untrusted hosts with leased IP addresses D. uses the DHCP snooping binding database to validate subsequent requests from untrusted hosts E. limits IP traffic on an interface to only those sources that have an IP-MAC address binding table entry or static IP source entry Answer: ACD QUESTION 146 A customer would like to monitor traffic that is being sent to a specific virtual machine named VM001 using SPAN. The customer has another virtual machine configured as a sniffer host called VM002. What configuration is required, and what other changes will need to be made? (Choose two.)

VSM-PRI-188# sh int vethernet 5 Vethernet5 is up Port description is VM001, Network Adapter 2 Hardware. Virtual, address: 0050.56b0.001e (bia 0050.56b0.001e) Owner is VM "VM001", adapter is Network Adapter 2 Active on module 5 VMware DVS port 484 Port-Profile is VM-vlan-10 Port mode is access VSM-PRI-188# sh int vethernet 6 Vethernet6 is up Port description is VM002, Network Adapter 1 Hardware. Virtual, address: 0050.56b0.0020 (bia 0050.56b0.0020) Owner is VM "VM002", adapter is Network Adapter 1 Active on module 5 VMware DVS port 485 Port-Profile is VM-vlan-10 Port mode is access A. Monitor session 1 type span Source interface veth5 both Destination interface veth6 No shut B. monitor session 1 source vlan 10 destination interface veth6 no shut C. monitor session 1 type er-span source

interface vlan 10 destination ip 10.1.1.10 no shutdown. VM002 must be removed from the N1k VEM. Move VM002 to Module 5F. Restart the VEM on module 5. Answer: AE QUESTION 147 Given a host with two NICs assigned to a N1k profile, which topologies are suitable for this type of configuration (Choose three.) port-profile type Ethernet name VM-Datavmware port-group switchport mode trunk switchport allowed vlan 400-410 channel-group auto mode active no shutdown state enabled A. Cisco UCS fabric interconnects B. Pair of N5K's in VPC C. Standalone N5K D. Pair of N5K's in non-VPCE. Cisco Catalyst 6000 Switch in VSS Answer: BCE QUESTION 148 Which statements are valid for a local SPAN configuration? (Choose two.) A. Source and destination interface must be on the same host B. Source and destination interfaces can be on different hosts C. Destination vEthernet interface can be on a different VLAN than the source D. Destination interface can be a physical port E. Destination interface cannot be a physical port Answer: AD QUESTION 149 What is the use of ERSPAN on N1k? A. Send monitored traffic to a VLAN B. Send monitored traffic to a remote VEM over L2 C. Receive monitored traffic on a vEthernet interface D. Send monitored traffic to an IP destination Answer: D QUESTION 150 Given the following configuration: port-profile type ethernet DATA-UPLINK vmware port-group switchport trunk allowed vlan 1-3967,4048-4093 channel-group auto mode on no shutdown state enabled port-profile type ethernet MGMT-UPLINK vmware port-group switchport trunk allowed vlan 10-12 channel-group auto mode on no shutdown state enabled VEMs are seen to be joining and then are lost from the Cisco VSM. How would you resolve this issue? A. Remove second NIC from each port profile B. Remove VEM from VSM (no vem X), remove NICs, and reinsert C. Ensure that VLANs on uplink profiles are not overlapping D. Reinstall VEM. Issue the command "module vem X execute vemcmd set pinning module vsm 1" Answer: C Braindump2go 350-080 Latest Updated Braindumps Including All New Added 350-080 Exam Questions from Exam Center which Guarantees You Can 100% Success 350-080 Exam in Your First Try Exam!

CCIE Data Center Written



Product Description
Exam Number: CCIE Data Center Written
"CCIE Data Center Written the complete collection through 394 Q&A cover every field successful Cisco"

Questions and Answers : 394 Q&As
Updated: Oct 12, 2015
\$429.99 **\$99.99**

[PDF DEMO](#)

[CHECK OUT](#)

[Printable PDF](#)

FREE DOWNLOAD: NEW UPDATED 350-080 PDF Dumps & 350-080 VCE Dumps from Braindump2go:
<http://www.braindump2go.com/350-080.html> (394 Q&A)