

## [March-2018-NewBraindump2go Free 300-180 PDF and 300-180 VCE Guarantee 300-180 Exam Pass[90-100

2018 March Latest Cisco 300-180 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-180 Real Exam Questions:1.|2018 Latest 300-180 Exam Dumps (PDF & VCE) 374Q&As Download:  
<https://www.braindump2go.com/300-180.html>2.|2018 Latest 300-180 Exam Questions & Answers Download:  
<https://drive.google.com/drive/folders/0B75b5xYLjSSNRfptN0xiTENBMzA?usp=sharing>QUESTION 90A UCS Admin is trying to launch the KVM console but it is failing to launch. All IP Pools for mgmt are configured and the CIMC has an address in UCSM. They SSH to the fabric Interconnect and run an ethalyzer while issuing a ping from their local PC to the KVM IP address. The ping is successful but they do not see the ICMP requests and replies displayed in the capture. Here is the filter they used:FIA(nxos)#ethalyzer local interface mgmt display-filter icmp limit-captured-frames 0What could be the reason pings are not seen in the capture and the KVM is failing to load?A. Java settings are preventing the KVM from loadingB. There is a duplicate IP address for that CIMC addressC. The switch upstream from the FI has the wrong vlan configuredD. The CIMC IP pool is in the same subnet as the Fabric Interconnects mgmt 0 interfaceAnswer: BQUESTION 91Where do you configure users so that they cannot access resources that belong to other organizations?A. rolesB. domain separationC. localsD. VDCsAnswer: CQUESTION 92What is the correct procedure to change Ethernet switching modes?A. Navigate to the subordinate Fabric Interconnect in the GUI, choose "Set Ethernet Switching mode", wait for it to come back up, and repeat on the primary FI.B. Navigate to either Fabric Interconnect in the GUI, choose "Set Ethernet Switching mode", and wait while both FIs reboot simultaneously.C. Navigate to either Fabric Interconnect in the GUI and transparently update the mode to switching. Repeat on the other Fabric Interconnect.D. Simply start using the switching features. The Fabric Interconnect automatically reconfigures to use Ethernet Switching Mode.Answer: BQUESTION 93Which power policy should be chosen to maximize the performance of a Cisco UCS system with four PSUs and eight blades?A. non-redundantB. N+1C. gridD. performanceAnswer: CQUESTION 94Which option describes why the service profiles do not inherit changes from the template?A. The service profile is not compatible with the changes.B. The changes to the template have not been committed.C. It is an initial template.D. The service profile has disabled inheritance.Answer: CQUESTION 95Which statement about Cisco UCS version compatibility is true?A. All bundles (A, B, and C) must be the same version.B. The B and C bundles must be the same revision.C. The A bundle can be one revision higher than the B/C bundles.D. The B/C bundles can be one revision higher than the A bundles.Answer: CQUESTION 96Which feature on the Cisco IMC GUI allows you to view the last boot post operation?A. Firmware Management tabB. Bootstrap Process RecordingC. Crash RecordingD. Trusted Platform ModuleAnswer: BQUESTION 97Which option is a valid file extension for a CIMC configuration file?A. .xmlB. .jsonC. .txtD. .exeE. .zipAnswer: AQUESTION 98Which three components are updated using the Host Upgrade Utility? (Choose three.)A. BIOSB. Network Adapter(s)C. Array ControllerD. Cisco IMCE. LOM portF. UCSMG. Drive FirmwareAnswer: ABDQUESTION 99Which option causes an operating system on a UCS device to consistently crash several minutes after booting?A. faulty power supplyB. out-of-date network adapter firmwareC. incompatible operating system driverD. incorrect boot orderE. disabled trusted platform moduleAnswer: CQUESTION 100Which two statements about configuring a traffic monitoring session are true? (Choose two.)A. You can set a local VM as a traffic destination.B. You can have up to two active monitoring sessions simultaneously.C. An unlimited number of monitoring session can be stored.D. A newly created monitoring session is enabled by default.E. A destination port can also be a source port within the same session.F. A vHBA can be a source for either an Ethernet or Fibre Channel monitoring session, but not both.Answer: BF!!!RECOMMEND!!!1.|2018 Latest 300-180 Exam Dumps (PDF & VCE) 374Q&As Download:<https://www.braindump2go.com/300-180.html>2.|2018 Latest 300-180 Study Guide Video: YouTube Video: [YouTube.com/watch?v=CAOPD5fGrmc](https://www.youtube.com/watch?v=CAOPD5fGrmc)