

[May-2019-NewFree Braindump2go 300-170 Dumps PDF Download 152Q

2019/May Braindump2go 300-170 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-170 Exam Questions:1.|2019 Latest 300-170 Exam Dumps (PDF & VCE) Instant Download:<https://www.braindump2go.com/300-170.html>

2.|2019 Latest 300-170 Exam Questions & Answers Instant

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNUIhkLWQ5UVdfaWM?usp=sharing>New QuestionRefer to the exhibit. You attempt to configure a local SPAN session on a Cisco Nexus 1000V Series Switch by using the vEthernet interface of VM1 as the source port and the vEthernet destination port. Which description of what happens to the SPAN session is true?A. It can be successfully only logged to a file on VEM1.B. It succeeds.C. Both VMs must be on same VLAN for this work.D. It fails.**Answer: D**

New QuestionRefer to the exhibit. Which two VRFs does Cisco NX-OS create by default? (Choose two.)A.

defaultB. managementC. PKAD. adminE. global**Answer: AB**New QuestionYou have a Cisco Nexus device that is configured to use RADIUS serve. What occur when local RBAC user account roles and RADIUS roles exist simultaneously?A. Only rules that are in the local roles and the RADIUS roles are appliedB. Only rules from the local roles are applied.C. Only rules from the RADIUS roles are applied.D. The rules from the local roles and the RADIUS roles are merged.**Answer: B**

New QuestionWhen running Cisco NX-OS, which description of route leaking between VRFs is true?A. By default the maximum number of IP prefixes that can be imported from the default VRF to a non-default VRF is 500.B. Route leaking can be restricted to specific routes by using a VASI interface.C. Route leaking is supported only between the default VRF and a non-default VRF.D. VRF route leaking requires an Enterprise license.**Answer: D**

New QuestionRefer to the exhibit. You must extend Layer 2 services out of the Cisco ACI fabric configuring contracts for the connected devices. Which options do you extend?A. EPG out of the ACI fabricB. Layer 2 domain by using remote VTEFC. bridge domain out of the ACI fabricD. VMM out of the ACI fabric**Answer: B**

New QuestionWhen configuring the SVS Domain in Layer 2 mode in he Cisco Nexus 1000v, which three parameter are required? (Choose three)A. port profileB. control VLANC. domain IDD. attributeE. packet VLANF. port group**Answer: BCE**

New QuestionWhich type of connection is supported by Layer 3 in the Cisco ACI fabric?A. eBGP over OSPFB. eBGP over EIGRPC. eBGP over RIPD. iBGP over EIGRP**Answer: A**

New QuestionWhen you provision a VDC, which command is used in VDC configuration mode?A. vrf context- <vrf name>B. boot-order <number>C. vdc resource template <vdc template name>D. vdc combined-hostname**Answer: B**

New QuestionRefer to the exhibit. What is the result of the configuration?A. It enforces the distributed firewall.B. It requires a reboot of the Cisco APIC before enabling the firewall rulesC. It removes firewall information from the Cisco AVS.D. It monitors all the TCP traffic without enforcing the firewall rules.**Answer: A**

New QuestionRefer to the exhibit. Which description of the state of the m-band management configuration is true?A. A contract named default is consumed by the m-band EPG. VLAN 10 is the m-band management VLAN.C. In-band management is functional.D. A bridge domain was not assigned.**Answer: B**

New QuestionWhich situation causes POAP to auto provision a switch?A. The startup configuration is corrupt.B. The switch is powered on after being offline for more than 48 hours.C. The startup configuration is missing.The startup configuration is corrupt, and you manually rebooted the switch**Answer: C**!!!RECOMMEND!!!

1.|2019 Latest 300-170 Exam Dumps (PDF & VCE) Instant Download:<https://www.braindump2go.com/300-170.html>2.|2019 Latest 300-170 Study Guide

Video Instant Download: YouTube Video: [YouTube.com/watch?v=AgCaggKbwg0](https://www.youtube.com/watch?v=AgCaggKbwg0)