

[NEW-642-035-Dumps100% Real Cisco 642-035 Exam PDF & VCE 175q&as-Braindump2go[111-120]

2016/12 New Cisco 642-035: Troubleshooting Cisco Unified Computing (DCUCT) Exam Questions Updated Today! Free Instant Download 642-035 Exam Dumps (PDF & VCE) 175Q&As from Braindump2go.com Today! 100% Real Exam Questions! 100% Exam Pass Guaranteed! 1. | 2016/12 New 642-035 Exam Dumps (PDF & VCE) 175Q&As Download:

<http://www.braindump2go.com/642-035.html> 2. | 2016/12 New 642-035 Exam Questions & Answers:

<https://1drv.ms/f/s!AvI7wzKf6QBjgTXBG4XYyqC6-T8u> QUESTION 111 Which two types of ports are MAC addresses when operating in switch mode? (Choose two.) A. uplink B. FEX C. server D. backplane Answer: AC QUESTION 112 A customer has Server1 working properly, configured to boot over SAN and with service profile SP1 assigned. This service profile is cloned to service profile SP2 and assigned to Server2. Before Server2 boots, which three actions need to be performed? (Choose three.) A. Check the WWPN that is assigned to the vHBAs on SP2. B. Check the MAC address that is assigned to the vNICs on SP2. C. Add two vHBAs and assign them to the proper VSAN. D. Add the pWWN of SP2 to the zoning on the SAN switch. E. Change the boot target on SP2. F. Change the IP address of the vNICs. Answer: ADE QUESTION 113

When configuring a traffic-monitoring session, which two guidelines are required to complete the task? (Choose two.) A. For Ethernet traffic, the destination must be an unconfigured physical port. B. For Fibre Channel, the destination must be a Fibre Channel uplink port. C. For Ethernet traffic, the destination must be an active port that is assigned to an existing VLAN. D. For Fibre Channel, the destination must be an inactive port on a VSAN. Answer: AB QUESTION 114

Which three send and receive locations an administrator can find the root cause for a network issue on the Cisco UCS domain? (Choose three.) A. between fabric interconnect and LAN or SAN B. between the FEX and fabric interconnect C. between each FEX on the Cisco UCS chassis D. between the host and FEX E. between fabric interconnects within the domain F. between the Cisco UCS chassis and system interconnects Answer: ABD QUESTION 115

Refer to the exhibit. When this configuration is entered on a fabric interconnect, which traffic is added as a source for a monitoring session?

```
UCS-A# scope eth-uplink
UCS-A /eth-uplink # scope fabric a
UCS-A /eth-uplink/fabric # scope interface mon-src
UCS-A /eth-uplink/fabric/interface/mon-src # set direction transmit
UCS-A /eth-uplink/fabric/interface/mon-src # commit-buffer
```

A. the ingress traffic on uplink port 1 on slot 3 B. the ingress traffic on uplink port 3 on slot 1 C. the egress traffic on uplink port 1 on slot 3 D. the egress traffic on uplink port 3 on slot 1 Answer: D QUESTION 116

Refer to the exhibit. Which command was executed on a Cisco UCS Fabric Interconnect in NX-OS mode to produce this output?

SERVER	INTERFACE	VSAN	FCID	PORT NAME	EXTERNAL	NODE NAME	INTERFACE
vfc1942	1	0x7b0021	20:00:00:25:b5:58:10:2e	20:00:00:25:ff:58:10:2e	fc2/2		
vfc2883	1	0x7b0006	20:00:00:25:b5:58:10:4f	20:00:00:25:ff:58:10:4e	fc2/3		
vfc3026	1	0x7b002c	20:00:00:25:b5:58:10:5f	20:00:00:25:ff:58:10:2f	fc2/1		
vfc3080	1	0x7b002b	20:00:00:25:b5:58:10:6f	20:00:00:25:ff:58:10:1f	fc2/1		
vfc3424	1	0x7b0088	20:00:00:25:b5:58:10:de	20:00:00:25:ff:58:10:4e	fc2/1		
vfc3427	1	0x7b006a	20:00:00:25:b5:a5:0a:0b	20:00:00:25:b5:a5:00:03	fc2/3		
vfc3513	1	0x7b00a4	20:00:00:25:b5:ca:1a:df	20:00:00:25:b5:ca:00:7f	fc2/3		
vfc3521	1	0x7b000b	20:00:00:25:b5:58:10:1f	20:00:00:25:ff:58:10:5f	fc2/2		
vfc3606	1	0x7b00a2	20:00:00:25:b5:ca:1a:ff	20:00:00:25:b5:ca:00:5f	fc2/2		

Total number of flogi = 11.

A. show flogi database B. show npv flogi-table C. show flogi D. show npv flogi-database E. show fcns database Answer: B QUESTION 117

Refer to the exhibit. A system administrator reviews the VIF paths and discovers an error. What is the cause of the error?



A. The server has no connection to the SAN. B. The server is still booting over SAN. C. The server is still booting over iSCSI. D. The server has the VIC with errors and needed to make an RMA. E. The switch that is connected the fabric interconnect has a port that is unavailable. Answer: C QUESTION 118

Which two actions do you need to take to configure jumbo frames on UCS Manager? (Choose two.) A. Choose QoS Policy Jumbo, choose the LAN tab, and set the MTU value to 9000. B. Choose QoS System Class, choose the LAN tab, and set the MTU value to 9000. C. Choose LAN Uplinks Manager, choose the LAN tab, and set the MTU value to the uplinks VLANs to 9000. D. Choose the vNIC, and on the Server Profile set the MTU value to 9000. E.

On the Admin tab, under Global Policy, enable Jumbo MTU Bytes.F. Go the fabric interconnect on the Equipment tab, right-click the port, and set the MTU value to 9000. Answer: BD QUESTION 119What task is required before adding traffic sources to a monitoring session? A. create a traffic monitoring sessionB. choose a source componentC. activate the sessionD. delete any earlier data collection Answer: A QUESTION 120Which CLI command should you use to promote the local fabric interconnect to primary? A. cluster primary forceB. cluster failover primaryC. cluster force primaryD. cluster failoverE. failover Answer: C !!!RECOMMEND!!! 1.Braindump2go|2016/12 New 642-035 Exam Dumps (PDF & VCE) 175Q&As Download: <http://www.braindump2go.com/642-035.html> 2.Braindump2go|2016/12 New 642-035 Study Guide: YouTube Video: [YouTube.com/watch?v=xDvSONx77Nw](https://www.youtube.com/watch?v=xDvSONx77Nw)