[NEW-642-035-DumpsHigh Quality 642-035 PDF and 642-035 VCE Dumps 175Q&As Free Share[81-90

2016/12 New Cisco 642-035: Troubleshooting Cisco Unified Computing (DCUCT) Exam Questions Updated Today!Free Instant Download 642-035 Exam Dumps (PDF & VCE) 175Q&As from Braindump2go.com Today! 100% Real Exam Questions! 100% Exam Pass Guaranteed! 1.|2016/12 New 642-035 Exam Dumps (PDF & VCE) 175Q&As Download: http://www.braindump2go.com/642-035.html 2.|2016/12 New 642-035 Exam Questions & Answers: https://ldrv.ms/f/s!AvI7wzKf6QBjgTXBG4XYyqC6-T8u QUESTION 81For a KVM session to be successful, which two of these need to be done? (Choose two.) A. The Cisco IMC IP address needs to be assigned on the Admin tab.B. The Cisco IMC IP

need to be done? (Choose two.) A. The Cisco IMC IP address needs to be assigned on the Admin tab.B. The Cisco IMC IP address needs to be in the same subnet as the management IP.C. The Cisco IMC needs to be upgraded to the same version as the UCS Manager.D. The server needs to be fully discovered. Answer: AD QUESTION 82A customer is configuring SAN pin groups in a Cisco UCS domain. The customer notices that pinning is not working and traffic from the vHBA is not passing over the Fibre Channel uplink port. Which of these must be done for pinning to work correctly? A. Include the SAN pin group in a vHBA policy and then include the vHBA policy in the service profile that is assigned to that server.B. Include the SAN policy in the Cisco UCS Manager to match with pin groups on the fabric interconnect.C. The customer must have Cisco UCS Manager version 2.0 or above.D. Fibre Channel switch mode needs to be configured first. Answer: A QUESTION 83Refer to exhibit. A Cisco UCS admin is troubleshooting an issue with a vNIC not coming up on a blade. When looking at the CLI of the "Fabric Interconnect", the admin runs this command to view the status of the interface. Which option describes a possible reason why the interface is stuck in an

"initializing" state?

A. The service profile is not applied to a blade.B. The VLANs defined on the vNIC are not defined on a matching uplink port. The uplink port is down.D. The QoS policy on the vNIC is invalid.E. The MTU on the vNIC is higher than the MTU configured in the QoS system class. Answer: C QUESTION 84Which two options are causes for failure of a Cisco C-Series server that is configured to boot from SAN? (Choose two.) A. The boot LUN ID is not 0.B. The ISCSI target is only available via one via one path through the network.C. C-Series does not support boot from SAN.D. The KVM dongle is attached to the front of the server with a USB stick installed.E. Under the FCoE properties on the vNIC adapter, the FCoE VLAN ID is set to 10.F. The boot table for fc0 has not been configured. Answer: DF QUESTION 85Which command on the Fabric Interconnect displays packet statistics for a given QoS group and MTU size? A. show policy-map interface ethernet x/yB. show queuing interface ethernet x/y show interface ethernet x/yD. show class-map type qosE. show interface queuing ethernet x/y Answer: B QUESTION 86A Cisco UCS admin is trying to integrate Cisco UCS Manager with Active Directory Authentication. After the configuration is done, the admin is still unable to log in using LDAP credentials. When running a debug on the Fabric Interconnect, this error is displayed: ldap_build_roles_and_locales_from_attr: No attr for usr profileWhich step was missed in the configuration? A. The LDAP provider was not configured correctly.B. The proper RBAC role(s) were not assigned to the user.C. Cisco UCS Manager 2.1 is required for LDAP integration.D. The "Attribute" field in Cisco UCS was left blank. Answer: B QUESTION 87Which three requirements are needed to configure a blade to boot successfully from Fibre Channel? (Choose three.) A. zoningB. LUN maskingC. WWPN device aliasD. boot from SAN policyE. SAN connectivity policyF. port assignmentG. target WWPN needs to be set in the boot from SAN policy Answer: ABD QUESTION 88Which description of a core file is true? A. It is generated by a system failure.B. It is generated by a process failure.C. It is generated by a component failure.D. It is generated by a hardware failure. Answer: B QUESTION 89Which logs are used to troubleshoot hardware failure? A. system event logB. audit logC. accounting logD. gateway logsE. system log Answer: A QUESTION 90A UCS Admin is trying to launch the KVM console but it is failing to launch. All IP Pools for mgmt are configured and the CIMC has an address in UCSM. They SSH to the fabric Interconnect and run an ethanalyzer while issuing a ping from their local PC to the KVM IP address. The ping is successful but they do not see the ICMP requests and replies displayed in the capture. Here is the filter they used:FIA(nxos)#

ethanalyzer local interface mgmt display-filter icmp limit-captured-frames 0What could be the reason pings are not seen in the capture and the KVM is failing to load? A. Java settings are preventing the KVM from loadingB. There is a duplicate IP address for that CIMC addressC. The switch upstream from the FI has the wrong vlan configuredD. The CIMC IP pool is in the same subnet as the Fabric Interconnects mgmt 0 interface Answer: B !!!RECOMMEND!!! 1.Braindump2go|2016/12 New 642-035 Exam Dumps (PDF & VCE) 175Q&As Download:http://www.braindump2go.com/642-035.html 2.Braindump2go|2016/12 New 642-035 Study Guide: YouTube Video: YouTube.com/watch?v=xDvSONx77Nw