

[Nov-2018Exam Pass 100% !Braindump2go 352-001 VCE Exam Dumps 650Q Instant Download[Q511-Q521

2018/November Braindump2go 352-001 Exam Dumps with PDF and VCE New Updated Today! Following are some new 352-001

Real Exam Questions:1.|2018 Latest 352-001 Exam Dumps (PDF & VCE) 650Q&As

Download:<https://www.braindump2go.com/352-001.html>2.|2018 Latest 352-001 Exam Questions & Answers

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNSUNBNi1aYkpfOTQ?usp=sharing>QUESTION 511 Which IEEE standard is commonly used at the data link layer for an access network, in an IoT environment?A. Wireless Regional Area NetworkB. Low-Rate Wireless NetworkC. Wireless Local Area NetworkD. Broadband wireless metropolitan Network

Answer: BQUESTION 512 Which option lists the cloud service models?A. Internet as a Service, Platform as a Service, and Storage as a Service.B. Infrastructure as a Service, Platform as a Service, and Storage as a Service.C. Infrastructure as a Service, Platform as a Service, and Software as a Service.D. Internet as a Service, Product as a Service, and Storage as a Service.E.

Internet as a Service, Platform as a Service, and Software as a Service.**Answer: C**QUESTION 513 Refer to the exhibit. A customer interconnected hundreds of branch offices into a single DMVPN network, with the HUB in the main data center. Due to security policies, the customer requires that the default route for all Internet traffic from the users at the branches must go through the tunnel and the only connections that are allowed to and from the branch router over the local internet circuit are the DMVPN tunnels.

Which two combined actions must you take on the branch router to address these security requirements and keep the solution scalable? (Choose two) A. Place the WAN interface in a front-door VRF, leaving the tunnel interface in the default routing instanceB. Protect the WAN interface by an inbound ACL that permits only IPsec-related trafficC. Implement a zone-based firewall that allows only IPsec-related traffic from zone UNTRUSTED to zone TRUSTEDD. Add a host route for the public IP address of each remote branch and HUB routers that points directly to the local ISP, and add a default route that points to the tunnel E. Use a floating default route with the preferred path over the tunnel and a backup path over the Internet natively**Answer: AB**

QUESTION 514 What is a design application of control plane policing?A. CPP protects the control plane from reconnaissance and or denial-of-service attacksB. CPP protects the forwarding plane by rate limiting excessive routing protocol trafficC. CPP protects the forwarding plane by allowing legitimate traffic and dropping excessive trafficD. CPP drop malformed packet that are sent to the CPU**Answer: A**QUESTION 515 A regional ISP is running MPLS TE. These tunnels are configured manually using paths.

Which technology centralizes the traffic engineering decisions to reduce operational complexity?A. BGP Link StateB. DiffServ-TEC. TE autobandwidthD. Shared Risk link Group**Answer: C**QUESTION 516 An operations engineer asks for your help with a new switching deployment. The engineer confirms that STP is enabled on an edge switch, and a particular port is connected to another switch. The switch is not receiving configuration BPDUs, although it appears that everything is functioning correctly in the network. What is the design explanation?A. Bridge Assurance is enabled on the portB. Storm control broadcast is enabled on the portC. REP is enabled on the portD. BPDU Guard is enabled on the port**Answer: C**QUESTION 517 What are two possible drawbacks of ending Loop-Free Alternate to support fast convergence for most destination IGP prefixes? (Choose two)A. The IGP topology might need to be adjustB. Loop-free alternate's convergence in less than 100 milliseconds is not possibleC. Loop-free alternate's are supported only for prefixes that are considered external tot the IGPD. Loop-free alternates are not supported in global VPN VRF OSPF instancesE. Additional path computations are needed**Answer: AE**QUESTION 518 Which option is a design consideration when using routers in a distributed hardware architecture?A. Routing information is stored in the RIB and the FIB makes forwarding decisions as programmed on the line card hardwareB. After a link failure occurs in the core, the RIB continues to forward the traffic while FIB convergence is in progressC. BGP routes are stored in the RIB and IGP routes are stored in the FIBD. IP routes are stored in the RIB and MPLS labels are stored in the FIB**Answer: A**QUESTION 519 Refer to the Exhibit. In which three Layers should you use nonstop Forwarding to reduce service impact in case of failure? (Choose three) A. Enterprise EdgeB. Enterprise CoreC. Service provider EdgeD. Dual-attached sever LayerE. Enterprise Non-Routed Access LayerF. Enterprise Non-Routed Distribution Layer**Answer: ABC**QUESTION 520 Which mechanism provides fast path failure detection?A. Non-Stop ForwardingB. Carrier delayC. Graceful restartD. UDLDE. Fast hello packetsF. iSPF**Answer: E**QUESTION 521 A financial trading organization plans to monitor the network latency for multicast data feeds on a hop-by-hop basis. Which technology should be added to their design to support this requirement?A. SPANB. NBARC. IPFIXD. Precision Time Protocol**Answer: D**!!!RECOMMEND!!!1.

2018 Latest 352-001 Exam Dumps (PDF & VCE) 650Q&As

Download:<https://www.braindump2go.com/352-001.html>2.|2018 Latest 352-001 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=EOsYo6HE8eQ](https://www.youtube.com/watch?v=EOsYo6HE8eQ)

2018 Latest 352-001 Exam Dumps (PDF & VCE) 650Q&As

Download:<https://www.braindump2go.com/352-001.html>2.|2018 Latest 352-001 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=EOsYo6HE8eQ](https://www.youtube.com/watch?v=EOsYo6HE8eQ)