

## [November-2018Free 200-310 Exam Dumps 551Q Questions and Answers New Updated By Braindump2go[Q168-Q178

2018/November Braindump2go 200-310 Exam Dumps with PDF and VCE New Updated Today! Following are some new 200-310

Real Exam Questions:1.|2018 Latest 200-310 Exam Dumps (PDF & VCE) 551Q&As

Download:<https://www.braindump2go.com/200-310.html>2.|2018 Latest 200-310 Exam Questions & Answers

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNmNsWnFEczRBdU0?usp=sharing>QUESTION 168What type of

topology supports WAN redundancy when a balance is required between cost, high availability, and performance?A. partial

meshedB. full meshedC. starD. ringE. hub-and-spokeF. bus G. point-to-point**Answer: A**QUESTION 169What is the

key limitation of using Internet circuits as a backup to a private enterprise WAN?A. circuit bandwidthB. prioritizationC.

securityD. operational expense**Answer: B**QUESTION 170A network design engineer is seeking a dynamic routing protocol that

supports fast convergence in a Cisco environment. What protocol allows for this?A. EIGRPB. OSPFC. RIPD. BGPE. IS-IS

**Answer: A**QUESTION 171What are two benefits of the bottom-up design approach? (Choose two.)A. allows a quick response to

a design requestB. facilitates design that is based on previous experienceC. requires little or no notation of actual organizational

requirements for implementationD. incorporates organizational requirementsE. provides a broader overview to the organization

and the designer**Answer: AB**QUESTION 172Which network layer is the best fit for security features such as DAI and DHCP

snooping?A. campus coreB. enterprise edgeC. campus distributionD. remote-access VPNE. enterprise data centerF.

campus access**Answer: F**QUESTION 173Directory services and electronic messaging are performed at which layer of the

network?A. coreB. applicationC. distributionD. network**Answer: B**QUESTION 174Refer to the exhibit. Which

configuration can be used to implement FHRP protocol and load balancing at the same time? A. R1Interface Ethernet0ip address

171.16.6.5 255.255.255.0standby 1 preemptstandby 1 ip 171.16.6.100standby 1 track Serial0standby 2 preemptstandby 2 ip

171.16.6.200standby 2 track serial 0standby 2 priority 95!!R2interface Ethernet0ip address 171.16.6.6 255.255.255.0standby 1

preemptstandby 1 ip 171.16.6.100standby 1 track Serial0standby 1 priority 95standby 2 preemptstandby 2 ip 171.16.6.200standby 2

track serial 0B. R1Interface Ethernet0ip address 171.16.6.5 255.255.255.0standby 1 preemptstandby 1 ip 171.16.6.100standby 1

track Serial0standby 1 priority 95!!R2interface Ethernet0ip address 171.16.6.6 255.255.255.0standby 1 preemptstandby 1 ip

171.16.6.100standby 1 track Serial0standby 1 priority 95C. R1Interface Ethernet0ip address 171.16.6.5 255.255.255.0standby 1

preemptstandby 1 ip 171.16.6.100standby 1 track Serial0standby 1 priority 95standby 2 preemptstandby 2 ip 171.16.6.200standby 2

track serial 0standby 2 priority 95!!R2interface Ethernet0ip address 171.16.6.6 255.255.255.0standby 1 preemptstandby 1 ip

171.16.6.100 standby 1 track Serial0standby 2 preemptstandby 2 ip 171.16.6.200standby 2 track serial 0D. R1Interface Ethernet0

ip address 171.16.6.5 255.255.255.0standby 1 preemptstandby 1 ip 171.16.6.100standby 1 track Serial0standby 1 priority 95!!R2

interface Ethernet0ip address 171.16.6.6 255.255.255.0standby 1 preemptstandby 1 ip 171.16.6.100**Answer: A**QUESTION 175

Cisco FabricPath brings the benefits of routing protocols to Layer 2 network Ethernet environments. What are two advantages of

using Cisco FabricPath technology? (Choose two.)A. Cisco FabricPath provides MAC address scalability with conversational

learning.B. Loop mitigation is provided by the TTL field in the frame.C. Cisco FabricPath technology is supported in all Cisco

platforms and can replace legacy Ethernet in all campus networks.D. Cisco FabricPath relies on OSPF to support Layer 2

forwarding between switches, which allows load balancing between redundant paths.E. Cisco FabricPath is IETF-standard and is

not used with Cisco products.**Answer: AB**QUESTION 176A network design shows two routers that are directly connected to an

Ethernet switch using optical connections. There is an OSPF adjacency between the routers. In this design, which solution ensures

that interface-down detection is reported as quickly as possible to the IGP?A. optimized OSPF SPF timersB. Bidirectional

Forwarding DetectionC. automatic protection switchingD. optimized OSPF LSA timersE. Ethernet OAM CFM monitoring

**Answer: B**QUESTION 177Which statement is true about using a DNS server to discover a controller IP?A. The AP sends a

discovery request to the first controller on the list and then goes down the list chronologically until it receives a discovery response.

B. The AP sends a discovery request to the last controller on the list and then goes up the list chronologically until it receives a

discovery response.C. The AP sends a discovery request to all controllers on the list simultaneously.D. Multiple controller IP

addresses in a DNS response are not supported.**Answer: C**QUESTION 178Refer to the exhibit. A network engineer at a technical

call center receives a call from a customer complaining that only 56 kbps of data can be transferred over the T1 Frame Relay WAN

circuit at a remote site. The engineer checks the Frame Relay switch and confirms that only 56 kbps is being transferred over the

circuit. The engineer requests the router configuration of the customer headquarters site router. What is causing this issue to occur?

A. The wrong CIR is configured.B. The BECN configuration is causing this issue.C. The class name is spelled wrong under

the interface.D. The wrong DLCI number is assigned to the interface.**Answer: C!!!RECOMMEND!!!**1.|2018 Latest 200-310

Exam Dumps (PDF & VCE) 551Q&As Download:<https://www.braindump2go.com/200-310.html2>,|2018 Latest 200-310 Study Guide Video: YouTube Video: [YouTube.com/watch?v=Qrsw1ousUGM](https://www.youtube.com/watch?v=Qrsw1ousUGM)