

## [November-2018Free Cisco 835Q 400-201 VCE Exam Dumps Braindump2go Offer[Q205-Q215

2018/November Braindump2go 400-201 Exam Dumps with PDF and VCE New Updated Today! Following are some new 400-201

Real Exam Questions:1.2018 Latest 400-201 Exam Dumps (PDF & VCE) 835Q&As

Download:<https://www.braindump2go.com/400-201.html>2.2018 Latest 400-201 Exam Questions & Answers

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNbGVFRUFuUW5TR2c?usp=sharing>QUESTION 205Which two routing protocols support MPLS traffic engineering link information distribution? (Choose two)A. OSPFB. BGPC. RIP version 2D. IS-ISE. EIGRPA**Answer: AD**QUESTION 206Two routers that are running MPLS and LDP have multiple links that than connect them to each other. An engineer wants to ensure that the label bindings are not flushed from the LIB if one of the links fails. Which configuration meets this requirement?A. the mpls ldp neighbor targeted commandB. the mpls ip command on a Cisco MPLS TE tunnelC. the mpls ldp discovery targeted-hello accept commandD. the mpls ldp session protection command**Answer: D**

Explanation:[http://www.cisco.com/c/en/us/td/docs/ios/12\\_0s/feature/guide/fssespro.html#wp1027177](http://www.cisco.com/c/en/us/td/docs/ios/12_0s/feature/guide/fssespro.html#wp1027177)

[http://www.cisco.com/c/en/us/td/docs/ios-xml/ios/mp\\_ldp/configuration/xs-3s/asr1000/mp-ldp-xe-3s-asr1000-book/mp-ldp-sesn-prot.html#GUID-FA0EF183-FA7C-488A-85C1-82BFEB91DCA7](http://www.cisco.com/c/en/us/td/docs/ios-xml/ios/mp_ldp/configuration/xs-3s/asr1000/mp-ldp-xe-3s-asr1000-book/mp-ldp-sesn-prot.html#GUID-FA0EF183-FA7C-488A-85C1-82BFEB91DCA7)QUESTION 207In which state can BGP peers exchange

Update messages?A. OpenConfirmB. OpenSentC. ActiveD. IdleE. Established**Answer: E**QUESTION 208Which statement about MPLS Traffic Engineering policy-based tunnel selection (PBTS) is not true?A. The tunnel that is not configured with the policy-class command acts as the default.B. EXP selection is between multiple tunnels to the same destinationC. There is no requirement for IGP extensionsD. Tunnels are configured using the policy-class command and carry multiple EXP values.E. It supports VRF traffic, IP-to-MPLS switching, and MPLS-to-MPLS switching**Answer: D**

QUESTION 209Refer to the exhibit. Both MPLS TE tunnel 14 and MPLS TE tunnel 124 pass over the same physical links. Which configuration on R1 enables TE 14 to be the primary tunnel and TE 124 to become active when TE 14 is admin disabled? A. Interface Tunnel14tunnel mpls traffic-eng priority 3 1!Interface Tunnel124tunnel mpls traffic-eng priority 5 4B. Interface Tunnel14tunnel mpls traffic-eng priority 4 1!Interface Tunnel124tunnel mpls traffic-eng priority 3 2C. Interface Tunnel14tunnel mpls traffic-eng priority 7 7!Interface Tunnel124tunnel mpls traffic-eng priority 1 1D. Interface Tunnel14tunnel mpls traffic-eng priority 3 2!Interface Tunnel124tunnel mpls traffic-eng priority 4 1**Answer: A**Explanation:Example:Router(config-if)# tunnel mpls traffic-eng priority 1 1Configures setup and reservation priority for a tunnel.The setup-priorityargument is the priority used when signaling an LSP for this tunnel to determine which existing tunnels can be preempted.Valid values are from 0 to 7. A lower number indicates a higher priority. An LSP with a setup priority of 0 can preempt any LSP with a non-0 priority.The hold-priorityargument is the priority associated with an LSP for this tunnel to determine if it should be preempted by other LSPs that are being signaled.Valid values are from 0 to 7, where a lower number indicates a higher priority.

[http://www.cisco.com/c/en/us/td/docs/ios-xml/ios/mp\\_te\\_path\\_setup/configuration/xs-3s/mp-te-path-setup-xe-3s-book/mp-te-verbatim-path-xe.html](http://www.cisco.com/c/en/us/td/docs/ios-xml/ios/mp_te_path_setup/configuration/xs-3s/mp-te-path-setup-xe-3s-book/mp-te-verbatim-path-xe.html)<http://wiki.kemot-net.com/mpls-te-path-setup-priority-hold>QUESTION 210What best explains the BGP route-reflector function?A. None of the above.B. BGP route-reflector does not have to be in the forwarding path of data coming from its clients.C. BGP route-reflector will stop reflecting the routes if they're not directly-connected clients.D. BGP route-reflector should be in forwarding path of data coming from its clients.**Answer: B**

QUESTION 211What is the importance of using Virtual Output Queues on ingress Line Cards in a high-end router?A. Increases forwarding performanceB. Simplifies configurationC. Prevents head-of-line blockingD. Uses less memory**Answer: C**QUESTION 212Which three BGP attributes are carried by TLV? (Choose three)A. Local PreferenceB. WeightC. OriginD. Network Layer Reachability Information (NLRI) E. Multiple Exit Discriminator (MED)**Answer: ADE**QUESTION 213Refer to the exhibit. Which statement is true? A. This is an interautonomous unicast route. B. The BGP MED value is 26.C. This is an mVPN route.D. The route target value is 10.1.100.2:3.E. There is a route reflector in this network.F. The route did not import this route into the VRF one.**Answer: E**

QUESTION 214A Service Provider is offering VoIP services and a service level agreement to customers. Which configuration provides validation to customers that the service level agreement has been honored?A. ip sla 999 udp-jitter 209.165.200.225 1000 codec g729a tos 160 ip sla schedule 999 life forever start-time nowB. ip sla 999 icmp-jitter 209.165.200.225 tos 160ip sla schedule 999 life forever start-time nowC. ip sla 999 icmp-jitter 209.165.200.225 tag VoIP-SLA ip sla schedule 999 life forever start-time nowD. ip sla 999 udp-jitter 209.165.200.225 1000 codec g729a tag VoIP-SLA ip sla schedule 999 life forever start-time now**Answer: A**Explanation:Setting tos 160 will mark VOIP packets as CS5.QUESTION 215Refer to the exhibit. ABC and XYZ MPLS VPN customers are accruing Internet access. Both CEs are sending traffic to the Internet. Which statement about their connectivity is true? A. Both CEs will have connectivity.B. Only CE-XYZ will have connectivity.C. Neither CEs will have

connectivity, as both CEs are using the same NATed subnet.D. Only CE-ABC will have connectivity.E. Neither CEs will have connectivity, as IAR does not have route back to the NATed subnet.Answer: AExplanation:If IAR has no OSPF config, both CEs have no connectivityIf IAR has OSPF config , both CEs have connectivity. Because the PE has OSPF config , we think the IAR has OSPF config too.!!!RECOMMEND!!!1.|2018 Latest 400-201 Exam Dumps (PDF & VCE) 835Q&As

Download:<https://www.braindump2go.com/400-201.html>2.|2018 Latest 400-201 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=7xgq2PoIXG0](https://www.youtube.com/watch?v=7xgq2PoIXG0)