

## [Sep-2020Free 300-625 300-625 85Q 300-625 Dumps PDF and VCE Braindump2go Offer[Q45-Q60

2020/Sep Latest Braindump2go 300-625 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-625 Real Exam Questions!QUESTION 45Refer to the exhibit.

```
switch-1 (config)# zoneset name Zone-B vsan 100  
Zoning database update is progressing. Command rejected
```

Which command is used to determine which switch has the lock?A. show fcs ie vsanB. show zoneset activeC. show zone statusD. show flogi database Correct Answer: CQUESTION 46Which command identifies the application and the user that have a Cisco Fabric Services session open?A. show cfs applicationB. show zoneset activeC. show cfs lockD. show device-alias database Correct Answer: AQUESTION 47A storage engineer is troubleshooting a Cisco MDS switch upgrade issue. What prevents the completion of a non-disruptive upgrade?A. The Fibre Channel host initiator is connected.B. The Fibre Channel storage target is connected.C. The Cisco Fabric Services operation in progress.D. The Fibre Channel and FCoE storage targets are connected. Correct Answer: BQUESTION 48Refer to the exhibits.

Exhibit 1:

```
MDS-A# show zoneset vsan 100  
zoneset name ZoneSetMDS-A-VSAN100- vsan 100  
MDS-A# show zoneset brief vsan 100  
zoneset name ZoneSetMDS-A-VSAN500 vsan 100  
zone Host1-Strg1  
zone Host2-Strg2  
MDS-A# show zoneset active vsan 100  
zoneset name ZoneSetMDS-A-VSAN100 vsan 100  
zone name Host1-Strg1 vsan 100  
pwn 20:00:00:25:b5:fa:00:11  
pwn 50:05:07:68:0d:05:ac:11  
pwn 20:00:00:25:b5:fa:00:22  
pwn 50:05:07:68:0d:05:ac:22  
MDS-A# show zone status vsan 100  
VSAN: 100 default-zone: deny distribute: active only Interop: default  
mode: basic merge-control: allow  
session: none  
hard-zoning: enabled broadcast: unsupported  
smart-zoning: disabled  
rscn-format: fabric-address  
activation overwrite control: disabled  
Output omitted for brevity
```

Exhibit 2:

```
MDS-A# show zoneset vsan 100  
zoneset name ZoneSetMDS-B-VSAN100- vsan 100  
zone Host1-Strg1 vsan 100  
pwn 50:05:07:68:0d:05:ac:33  
MDS-A# show zoneset brief vsan 100  
zoneset name ZoneSetMDS-A-VSAN100 vsan 100
```

A storage network engineer activates a zoneset on MDS-A and verifies the successful activation (Exhibit 1). The engineer is then notified that there is a SAN outage (Exhibit 2) What is the cause of the outage?A. Another network engineer activated zoneset ZoneSetMDS-B-VSAN100 on MDS-A.B. Another network engineer issued the zone mode enhanced vsan 100 command on another switch in the fabric.C. Another network engineer activated the zoneset ZoneSetMDS-B-VSAN100 command on another switch in the fabric.D. Another network engineer issued the zone default-zone permit vsan 100 command on another switch in the fabric. Correct Answer: DQUESTION 49Refer to the exhibit.

```
MDS-A# show run interface port-channel 2  
interface port-channel2  
channel mode active  
switchport description ***Connected to FI***  
switchport rate-mode dedicated  
MDS-A# sh port-channel database  
Administrative channel mode is active  
Operational channel mode is active  
Last membership update succeeded  
First operational port is fcl/9  
2 ports in total, 2 ports up  
Ports: fcl/9 [up] *  
fcl/10 [up]
```

A port channel has been configured between a Cisco MDS and a Cisco Fabric Interconnect switch. Which interface(s) in the port channel carry the control plane traffic?  
 A. per packet, balanced between interfaces fc1/9 and fc1/10B. from interface fc1/9C. from interface fc1/10D. per flow, balanced between interfaces fc1/9 and fc1/10  
 Correct Answer: D  
 QUESTION 50A storage administrator is upgrading Cisco NX-OS on a Cisco MDS switch. The administrator performs an ISSU upgrade following the configuration guide. While the install is proceeding, the administrator connects a new server to the switch, which cannot access storage. The existing servers continue to operate properly through the switch. Why is the new server failing to connect?  
 A. The fabric data plane resets as part of the upgrade process.B. The new server is unable to log in to the fabric to receive an FC-ID.C. The upgrade process disables any currently unused ports.D. The zoning database is locked during the upgrade process.  
 Correct Answer: D  
 QUESTION 51Refer to the exhibit.

```

MDS-A# show run
...
!Activate Zone Database Section for vsan 10
zone name Server11 vsan 10
 member pwn 11:11:11:11:11:11:11:11
 member pwn 11:11:11:11:11:11:11:12
zoneset name Zoneset10-A vsan 10
 member Server11
zoneset activate name Zoneset10-A vsan 10
...

MDS-B# show run
...
!Activate Zone Database Section for vsan 10
zone name Server11 vsan 10
 member pwn 11:11:11:11:11:11:11:11
 member pwn 11:11:11:11:11:11:11:12
 member pwn 11:11:11:11:11:11:11:13
zoneset name Zoneset10-B vsan 10
 member Server11
zoneset activate name Zoneset10-B vsan 10

MDS-A# show interface fc1/11
fc1/11 is trunking (Not All VSANs UP on the trunk)
Port description is *** ISL-Trunk-MDS-B ***
...
Port mode is TE
Port vsan is 20
...
Trunk vsans (admin allowed and active) (10,20)
Trunk vsans (up) (20)
Trunk vsans (isolated) (10)
Trunk vsans (initializing) ()
...

MDS-A# show log
...
... MDS-A %ZONE-2-SS_MERGE_FULL_DATABASE_MISMATCH: %SVSAN 10% Zone merge full database
mismatch on interface fc1/11
... MDS-A %ZONE-2-SS_MERGE_FAILED: %SVSAN 10% Zone merge failure, isolating interface
fc1/11 reason: Member mismatch:(reason:0)
... MDS-A %PORT-5-IF_TRUNK_DOWN: %SVSAN 10% Interface fc1/11, vsan 10 is down
(Isolation due to zone merge failure) *** ISL-Trunk-MDS-B FC1/11 ***
    
```

A storage network engineer gets remote access to two Cisco MDS 9000 Series Switches with an ISL trunk and receives several log messages. Which set of actions resolve the problem while least affecting service?  
 A. 1. Add :11:11:11:11:11:11:11:13 pwn in zone Server11 and activate Zoneset10-A on MDS-A.2. shut/no shut interface fc1/11 on MDS-A.B. 1. Deactivate zone set Zoneset10-A on MDS-A.2. shut/no shut interface fc1/11 on MDS-A.C. 1. Add :11:11:11:11:11:11:11:13 pwn in zone Server11 and activate Zoneset10-A on MDS-A.2. Remove VSAN 10 from the allowed VSAN range of interface fc1/11 on MDS-A and add it back in the range.D. 1. Explicitly import zone set Zoneset10-A on MDS-B using the zoneset import interface import fc1/11 vsan 10 command.2. Activate the zone set Zoneset10-A.  
 Correct Answer: A  
 QUESTION 52DRAG DROPDrag and drop the boot issues from the left onto the correct solutions on the right.  
 Select and Place:

The BIOS is corrupted.	Replace the module.
The bootflash is corrupted.	Specify the entire path.
Boot parameters are incorrect.	Use the netboot option.
The Cisco NX-OS image is corrupted.	Recover by using the boot loader.

Correct Answer:

The BIOS is corrupted.	The BIOS is corrupted.
The bootflash is corrupted.	Boot parameters are incorrect.
Boot parameters are incorrect.	The bootflash is corrupted.
The Cisco NX-OS image is corrupted.	The Cisco NX-OS image is corrupted.

QUESTION 53A domain ID conflict is detected on a switch. Which action resolves the issue in the shortest possible time after the

preferred domain ID is changed to a static domain ID?A. Issue an fcdomain disruptive restart.B. Issue an fcdomain nondisruptive restart.C. Enter the commands for a VSAN suspend / no-suspend.D. Enter the commands to complete a domain manager fast restart.  
Correct Answer: AQUESTION 54Refer to the exhibit.

```
switch-2# show zone status vsan 10
VSAN: 10 default-zone: deny distribute: active only Interop: default
mode: enhanced merge-control: allow
Default zone:
 qos: none broadcast: disabled ronly: disabled
```

A user who is logged in as an operator cannot update the zoneset. What is the cause of this issue?A. The fabric is locked by admin on switch-2.B. Hard zoning is enabled.C. Merge control is disabled.D. The switch has a conflicting domain ID.E. The fabric is locked by admin on another switch.  
Correct Answer: AQUESTION 55After a subordinate switch requests a domain ID form a principal switch, the requested domain ID becomes the runtime domain ID, and all interfaces on the affected VSAN are isolated.

What is a solution to the issue?A. Add the received ID to the allowed list.B. Configure a static domain on the subordinate switch and reboot the switch.C. Enable the FICON feature on the affected VSAN.D. Configure IVR NAT on the affected VSAN.  
Correct Answer: AQUESTION 56The principal switch on a Fibre Channel network fails to assign requested domain to a subordinate switch. What are two reasons? (Choose two.)A. Cisco Fabric Services distribution is not enabled on the switch.B. The fabric is locked.C. The requested domain is outside the allowed list.D. The persistent FC ID feature is not enabled.E. An existing switch already has the requested domain assigned. Correct Answer: CEQUESTION 57A storage administrator is connecting two previously configured switches to make a single fabric. When the E Ports are connected, the administrator sees a ZONE MERGE FAILURE message referring to the zoneset for VSAN 10 on each switch. Which command should the administrator use to allow these switches to work together?A. zoneset import interface fc1/1 vsan 10B. zoneset distribute full vsan 10C. zoneset overwrite-control vsan 10D. zoneset copy active-zoneset full-zoneset Correct Answer: AQUESTION 58A storage administrator manually configures a storage switch to use a new static domain ID. After issuing an fcdomain restart vsan 1 command, the administrator sees that the switch is still using the existing domain ID. What is the reason why the configuration is not working?A. Static domain IDs apply only after a switch is rebooted.B. The disruptive keyword was not used on the command.C. Build fabric notifications were not sent to the other switches.D. Domain manager fast restart is not enabled on the switch.  
Correct Answer: AQUESTION 59Two stable fabrics have overlapping domains. After a switch from the first domain is joined to a switch from the second domain, both switches become isolated. What caused the problem?A. The autoreconfigure option is disabled on both switches.B. The autoreconfigure option is enabled on both switches.C. The rcf-reject option is enabled on the interfaces.D. The rcf-reject option is disabled on the interfaces.  
Correct Answer: AQUESTION 60A storage network engineer is upgrading a Cisco MDS Director with dual supervisor modules. The install command is executed on the standby supervisor module but fails. Which action would have prevented this failure?A. All FCoE interfaces configured on the MDS must be shut down before starting the upgrade.B. The upgrade must be done on the active supervisor module only.C. Cisco Fabric Services must be disabled before starting the upgrade.D. Fabric Controller Service must be stopped before starting the upgrade.  
Correct Answer: BResources

From: 1.2020 Latest Braindump2go 300-625 Exam Dumps (PDF & VCE) Free Share:

<https://www.braindump2go.com/300-625.html>2.2020 Latest Braindump2go 300-625 PDF and 300-625 VCE Dumps Free Share:

[https://drive.google.com/drive/folders/1ia0rBm00X02HtS8cWbiENI17ZcaNeP\\_B?usp=sharing](https://drive.google.com/drive/folders/1ia0rBm00X02HtS8cWbiENI17ZcaNeP_B?usp=sharing)3.2020 Free Braindump2go 300-625

PDF Download:[https://www.braindump2go.com/free-online-pdf/300-625-Dumps\(38-48\).pdf](https://www.braindump2go.com/free-online-pdf/300-625-Dumps(38-48).pdf)

[https://www.braindump2go.com/free-online-pdf/300-625-PDF\(27-37\).pdf](https://www.braindump2go.com/free-online-pdf/300-625-PDF(27-37).pdf)

[https://www.braindump2go.com/free-online-pdf/300-625-PDF-Dumps\(1-15\).pdf](https://www.braindump2go.com/free-online-pdf/300-625-PDF-Dumps(1-15).pdf)

[https://www.braindump2go.com/free-online-pdf/300-625-VCE\(16-26\).pdf](https://www.braindump2go.com/free-online-pdf/300-625-VCE(16-26).pdf)

[https://www.braindump2go.com/free-online-pdf/300-625-VCE-Dumps\(49-60\).pdf](https://www.braindump2go.com/free-online-pdf/300-625-VCE-Dumps(49-60).pdf)Free Resources from Braindump2go, We Devoted to Helping You 100% Pass All Exams!